

CARE AND FEEDING OF MAG FOR DUST CONTROL

Getting Started:

There are an infinite number of blends of footing materials that are used by equestrians in indoor arenas. The common problem in all footings is that they start out great but over time quickly develop nuisance dust because the footing is pulverized by the hoof action of constant riding and pounding.

Footings are a very individual thing. Some may prefer a “Palomino” mix of sand and stone dust, while others want a blend of wood, sand, and stone dust, and others want only crumb rubber or chip rubber and sand. There is no limit to the formulas of footings for each individual facility. The common denominator is that over time they ALL break down, and dust becomes a problem. Even rubber products will break down and eventually become airborne dust particles. Hunter Jumper arenas want footings that are firm but cushy while dressage arenas want a highly consistent footing with about 3-4 inches of loose footing on the surface.

The Problem:

The US Department of Labor has some staggering statistics about the ill effects of dust and respiratory illnesses caused by it. Nearly every riding arena has sand of some type somewhere in it; either as part of the subsurface or base, or as part of the footing itself. Sand contains silica, and silicosis is a well-documented INCURABLE disease that is caused by inhalation of airborne silica, or sand. Wood fibers also are a very real health problem. Consider that when the maximum permissible dust levels in the average woodshop are exceeded, OSHA or local health authorities are not only permitted but are required by law to shut down the facility until the dust is mitigated.

The Solution:

While there are many types of dust, all dust is the result of the material becoming so finely pulverized that it can become airborne and consequently inhaled. The easiest way to mitigate dust problems is with the addition of water to weigh down the particles and prevent them from floating.

Water is a viable solution (pun intended) for dust problems in many areas, but it does not come without costs. You must have the water or purchase it, then dispense it with a sprinkler system, and then that sprinkler system must be maintained, which means pumps, pipes, hoses, and potential plumbing problems.

Enter MAG, a proven humectant or hygroscopic agent that draws in moisture naturally. MAG is a form of magnesium chloride that is harvested from the Dead Sea, a source of life giving minerals. MAG will draw in water and then hold it at an impressive rate. One pound of MAG can hold up to four times its weight in water under ideal conditions. MAG will draw in moisture continuously and indefinitely and suppress dust permanently in any type of footing in any indoor arena.

Method:

Applying MAG to an indoor ring is all art and little science. Recognizing that footings are very individual, the objective in all footings is to maintain a consistent level of loose material to provide the desired amount of give.

The objective of proper dust control using MAG is to “sneak up” on the correct amount and NOT OVERAPPLY. When applying the product, always apply conservative amounts over a period of weeks, allowing ring use to mix the product into the footing to achieve the desired level of dust control.

Do Not Water!!!

The worst thing that you can do when using MAG is to water your ring. Once you commit to using MAG, it is very important that all watering for dust control is halted. The reason is simple: You are applying a dust control agent at the surface, and gravity and hoof action will help it to penetrate the footing, coat all the particles of footing and hold them down on the arena floor where you want them. By watering after you have applied MAG, you are rinsing the product off the top and into the subsurface.

How Much MAG do I need?

The amount needed varies depending upon your ring, but generally speaking, we find that it takes 2 to 4 pallets of MAG to achieve complete dust stabilization. ***Once the ring is completely stabilized you NEVER need to water again.*** In fact, watering the ring after it is stabilized with MAG is counterproductive and only rinses the dust control agent into the base where it does you no good. We recommend a maintenance dose of approximately one pallet per year to touch up around doorways where traffic and rain may remove the treated footing, and also to combat dust arising from other materials that are added to the indoor arena such as contaminants from boots, hooves, and manure.

Is it Safe to Use?

MAG is very safe to use and handle. The Occupational Safety and Health Administration (OSHA) uses a document called a “Material Safety Data Sheet” (MSDS) to standardize information about all materials. On this form OSHA uses an industry standard for toxicity called an “LD50”, which is the amount of material that is required to kill at least 50% of the test subjects. While this is a morbid thought, it is the standard that the government has established and is recognized industry wide. The LD50 for strychnine, a rat poison, is 16 (milligrams per kilogram of body weight). The LD 50 for aspirin and calcium chloride is 1000 mg/kg. The LD50 for table salt is 3,000, and the LD50 for MAG is 8,100! That means that MAG is 2.5 times less toxic than table salt, is about half as toxic as baking soda and is very comparable to vitamin C, ascorbic acid.

How long will it last?

MAG will last forever, or until you wash it away with water or add new footing.

How do I maintain my footing once it is fully stabilized?

This is the most important part of any successful program; Maintenance. You change the oil in the tractor, the car, and grease and maintain all the other tools of horse management so why wouldn't you also maintain your riding surface? We recommend that you regularly groom your riding surface with either a tine harrow or other drag-type device which will pull the footing up from the base and turn it over. Even an old piece of chain link fence dragged behind a machine will smooth out and level the riding surface. More often than not, the highest levels of dust are seen when grooming an untreated indoor ring. The best grooming devices are ones which have “teeth” that will dig into the footing and fluff it and turn it over while smoothing it out at the same time.

So, regular grooming is the #1 way to properly maintain your indoor ring once it is treated for dust. Next, a small maintenance dose of MAG for use around the doorways and problem areas is recommended. The average 100 X 200 indoor ring will take three pallets of MAG to fully stabilize and then one pallet of MAG per year to maintain. Compare these costs to the costs of a sprinkler system and frozen footing in the winter.

Frozen Toes Made you close?

There is a side benefit to MAG stabilization that has not been mentioned: freeze proofing your ring. You will never again be forced to shut down in winter because the water saturated footing in your indoor froze up, and you could not ride in it because it is like a frozen moonscape. MAG will keep the same consistency in your footing throughout the year including those sub-zero days when you were not able to ride because the indoor was hard as a stone.

Is MAG the same as the liquid stuff being offered?

No! MAG is not a liquid – it's dry flake form! Recently, others have begun to try to capitalize on the enormous success of our MAG. Some companies now offer a modified liquid product which appears to be a blend of unknown waste corn or agricultural chemicals and claimed to be mixed with an unknown source of magnesium. Do not be misled by others claiming to offer the performance of our MAG magnesium chloride in liquid form. It's impossible to have the same performance of a dry product in liquid form, even if you were to liquefy MAG and then mix it with something else. These are not MAG which is a registered trademark of Dead Sea Works and ONLY MAG offers the absolute performance guarantee for dust control in your footing.

ONLY MAG products have the benefit of experience of more than 15 years of use in Europe and New England. These unknown liquids are new to the market, are unproven, and there is NO TOXICOLOGICAL DATA on them as to long term effects on equine health in legs and hooves over a long period of time. Know what you are buying and be sure to demand a certificate of analysis which certifies the minimum $MgCl_2$ content. Our MAG is guaranteed to be 100% $MgCl_2$, hexahydrate while liquids chemically cannot contain more than 33% $MgCl_2$. There are NO agricultural or distiller's waste products in MAG; it is a pure natural product that is extracted from the Dead Sea – a source of life giving minerals. The costs of these liquids seem to average \$0.15-\$0.30/ft², which is equal to about \$2000 per treatment and \$3000 per year on the average indoor. That is more than five times as expensive as MAG! **Don't be fooled by imposters who are claiming to perform the same as our MAG!**

Nuts and Bolts – How to put it down: The term “this is not rocket science” comes to mind first. Think of applying MAG to your indoor as though you are fertilizing your lawn. You want to get even, thorough coverage. To do this we recommend the use of a broadcast spreader, or rotary spreader. We have had excellent results using a Brinly 150 lb. spreader that Home Depot sells for less than \$200.00. It is mostly plastic with stainless steel knife gate and application adjustments.

Using a rotary spreader, fill the spreader to capacity and begin at the far end of the arena away from the “stockpile” of MAG. Open the spreader up to full capacity (wide open) and then begin by making a checkerboard pattern going first north and south in your arena and then east and west over the same area in a checkerboard pattern. When

MAG is properly applied, it will look like it just snowed a light snow in the indoor. You will immediately see MAG start to pull in moisture and dissolve into the footing. This is what it's supposed to do and what will effect dust control. Start off by putting a rate of 2.5# per square yard of surface.

To determine your square yards, take the width times the length divided by 9. Multiply that number by 2.5 to determine what you will need for an initial dose. See the example below:

100' wide times 200' long = 20,000 square feet
20,000 square feet divided by 9 = 2,222 square yards
2,222 square yards times 2.5 lbs. per yard equals 5,555 lbs. of MAG for the first application.*

*This is only the first application but because all footings are different, and dust levels vary widely, this is a starting point that is more than half way to complete control for the average indoor. Next we suggest that you “sneak up” on the final amount needed for complete dust control in your indoor. Continue to add MAG but do so at much lower levels until you have achieved complete dust control. The second, and all subsequent applications, should be at approximately 1000 lbs. over the entire indoor. It is very important to not over-treat. Over-treating will result in a fully saturated, muddy, slippery, wet footing, that will compact and work against you. If you do make a mistake, and one week after treating find that you have over treated your indoor, then use a sprinkler to rinse away some of the product and drive it into the subsurface. This must be done with great care to avoid over rinsing and losing the job that you just worked so hard to do. With so many different types of footing, it is impossible to speculate about how much MAG it will take to stabilize or how much water it will take to “remove” some of the MAG that was over applied. As stated up front, this is not rocket science, and as a stable owner and barn manager, you know better than anyone that common sense is the best guide.

Realize that a treated ring needs some time to equilibrate or settle. While the first day after the first treatment you may think that you are all set, we find that a week or two later dust may begin to break through a little as the fines underneath the surface begin to work up and need to be treated. Typically a small maintenance dose of MAG is required from time to time to suppress new fines as they develop in normal ring use and around doorways and entries where rain may wash away some of the treatment, or where dirt and other sources of dust are dragged in to the arena.

Summary:

1. Prepare your ring to be treated by grooming and leveling.
2. Use a checkerboard pattern to apply product evenly.
3. **Do Not Water - Ever!** (It is ok to “spritz” the ring *once*.)
4. Thoroughly rinse down all equipment after each application. Ask for our brochure to understand more about this extremely safe and proven dust control product.

Solutions – 800-637-4504 – Your source for total dust control on riding surfaces

Packaged in 50 lb. bags and available in either flake or pellet forms.



Easily applied using a tow behind broadcast spreader.



Solutions – 800-637-4504 – Your source for total dust control on riding surfaces

When properly applied, it will look like it just snowed lightly on the indoor.



The photo below shows some flakes that were thrown over on to the cement aisle floor have already begun to draw in moisture and dissolve. This is how MAG works to coat dust particles and hold them down on the arena floor.



Initial treatment of a ring should look like this following application.



Solutions – 800-637-4504 – Your source for total dust control on riding surfaces

Within 24 hours, the MAG will dissolve and will wet the ring surface down. This will continue to improve and penetrate the footing as hoof traffic and use drives the product into the footing.



MAG[®]

800-637-4504



Solutions – 800-637-4504 – Your source for total dust control on riding surfaces